



Product information:

**TEBAS**  
BRIDGE TYPE

**SPECIFICATIONS**

	TEBAS
Table length - mm	4.100 – 6.100
Table width - mm	2.200 (2.500)*
Distance between columns - mm	3.000 (3.500)*
Longitudinal travel - mm	4.000 - 6.000
Cross travel - mm	3.750 (4.250)*
Vertical travel - mm	1.250 (1.500)*
Max. distance from table to spindle nose - mm	1.465 (1.765)*
Working Feed - mm/min	up to 30.000
Rapid feed - mm/min	50.000
Drives of X-Y-Z - mm	X,Y: Two motors rack and pinion Z: 2 Ball screws
Power - kW	43
Speed of the spindle head - min <sup>-1</sup>	4.500 - 6.000
Positioning and repeatability accuracy - mm	0,008/4.000-0,005
Tool magazine	30 (40-60-80)*
Allowed weight on the table - kg	20.000 - 35.000
Approx. net weight - kg	40.000 - 65.000

(Optional) \*

**ACCESSORIES**

	TEBAS
<b>HEADS</b>	
45° Automatic Head 360.000 pos, 0,001°	•
30° automatic head 360.000 pos. 0,001° and / or continuous rotation	○
30° automatic head, 360.000 positions each 0,001° and/or continuous rotation with electrospindle.	○
Direct Outlet head	○
Extended "L" shaped head	○
Change of heads	•

**TEBAS**

Coolant tank

1.000 l - 30 l/min - 14 bar 60 l/min - 5 bar

Chip Conveyor

•

- Standard
- Optional
- No available

**HEAD IMAGES**



45° Automatic Head  
360.000 pos, 0,001°



30° automatic head  
360.000 pos. 0,001° and /  
or continuous rotation



30° automatic head,  
360.000 positions each  
0,001° and/or continuous  
rotation with  
electrospindle.



Direct Outlet head



Extended "L" shaped  
head

**RELATED APPLICATIONS**



**INVAR MOULD  
FIXTURE**  
AERONAUTIC



**STRUCTURALS PARTS**  
AERONAUTIC




**ROTOR**  
WIND ENERGY



**BOGIE**  
RAILWAY



**CAPITAL GOODS**  
GENERAL MACHINING



**MACHINE TOOL**  
GENERAL MACHINING



**MOULD**  
MOULDS AND DIES



**DIE**  
MOULDS AND DIES



**CAPITAL GOODS**  
LARGE COMPONENTS

Más información en [www.zayer.com](http://www.zayer.com)