



Product information:

30KF / 30KFU
BED TYPE

SPECIFICATIONS

	30KF	30KFU
Table length - mm	3.000 - 5.000	
Table width - mm	1.000 (1.300)*	
Longitudinal travel - mm	2.700 - 4.700	
Cross travel - mm	1.250 (1.600)*	
Vertical travel - mm	1.500 (2.000)*	
Min – max distance from table to spindle nose - mm	0-1.445 (1.945)*	
Rapid feed - mm/min	20.000	
Working Feed - mm/min	6 - 10.000	
Drives of X,Y,Z, axis	X: B / 80	
B= Ball screw / Ø mm	Y: B / 80	
R= Rack / Module	Z: B / 80	
Power - kW	37	
Speed of the spindle head - min ⁻¹	35-3.000 (4.500-6.000)*	
Positioning and repeatability accuracy - mm	0,008/4.000 0,005/4.000	
Tool magazine	-	30 (40-60-80-100)*
Allowed weight on the table - kg	10.000	
Approx. net weight - kg	30.000 - 40.000	

(Optional) *

ACCESSORIES

	30KF	30KFU
HEADS		
45° Manual Head	•	—
45° Automatic Head 360.000 pos, 0,001°	○	•
Direct Outlet head		○
Movable quill Ø 175 x 500 mm		○
Change of heads		○
Change of Pallets		—
Chip Conveyor		○

30KF **30KFU**

Coolant tank

500l 60l/min 2,5bar

- Standard
- Optional
- No available

HEAD IMAGES




45° Manual Head



45° Automatic Head
360.000 pos, 0,001°



Direct Outlet head



Direct outlet head with quill

RELATED APPLICATIONS



FRANCIS TURBINE
HYDROELECTRIC



MOULD
MOULDS AND DIES



DIE
MOULDS AND DIES

More information at www.zayer.com