



Product information:

20KM / 20KMU
MOVING COLUMN

SPECIFICATIONS

| | 20KM | 20KMU |
|--|----------------------------|----------------|
| Table length - mm | 3.700-4.700 | |
| Table width - mm | 1.200 | |
| Longitudinal travel - mm | 2.400-3.400 | |
| Cross travel - mm | 1.250 (1.500)* | |
| Vertical travel - mm | 1.000 (1.500)* | |
| Min – max distance from table to spindle nose - mm | 0-934 (1.434)* | |
| Working Feed - mm/min | 6 - 10.000 | |
| Rapid feed - mm/min | 20.000 | |
| Drives of X,Y,Z, axis | X: B / 80 | |
| B= Ball screw / Ø mm | Y: B / 80 | |
| R= Rack / Module | Z: B / 80 | |
| Power - kW | 28 | |
| Speed of the spindle head - min ⁻¹ | 35-3.000 (4.500-6.000)* | |
| Positioning and repeatability accuracy - mm | 0,008/4.000 0,005/4.000 | |
| Tool magazine | - | 30 (40-60-80)* |
| Platform for the operator | - | |
| Allowed weight on the table - kg | 3.500 / m ² | |
| Approx. net weight - kg | 30.000-62.000 | |

(Optional) *

ACCESSORIES

| | 20KM | 20KMU |
|---|------|-------|
| HEADS | | |
| 45° Manual Head | • | — |
| 45° Automatic Head 360.000 pos, 0,001° | ○ | • |
| Movable Quill | | — |
| Direct Outlet head | | ○ |
| Change of heads | | ○ |
| Coolant tank | | ○ |

20KM | **20KMU**

Chip Conveyor

○

- Standard
- Optional
- No available

PRODUCT IMAGES



Protecciones CE



Protecciones CE y mampara de separacion para trabajo pendular

HEAD IMAGES



45° Manual Head



45° Automatic Head
360.000 pos, 0,001°



Direct Outlet head



Extended "L" shaped head with manual change of tool

RELATED APPLICATIONS

Más información en www.zayer.com