

龙门式 / BRIDGE TYPE

ARES 5000



工作尺寸 / WORKING DIMENSIONS

纵向行程 Longitudinal travel	5000	mm
横向行程 Cross travel	3850	mm
垂直向行程 Vertical travel	1200	mm
移动横梁 · 行程 Cross beam travel	900	
工作台面 Table surface	5000 x 2500	mm
立柱间距离 Distance between columns	3250	mm
工作台到主轴鼻端最小最大距离 Max. distance from table to spindle nose	1740	mm

线轴容量 / CAPACITY OF LINEAR AXIS

纵轴驱动 Longitudinal axis drive	双电机齿条齿轮 Rack and double motor and pinion	
纵横轴驱动 Cross and vertical axes drive	滚珠轴承 Ball screw	
工作进给 Working feed	30000	mm/min
快速进给 Rapid feed	25000	mm/min

CNC数控机床

MITSUBISHI M850W



铣头
HEAD

45° 电主轴
45° continuous rotation

功率 43 kW
Power

主轴头速度 7000 rpm
Speed of the spindle head



附件
ACCESSORIES

刀库 60
Tool magazine

冷却设备 6÷37 + 5 bar, 1000 l
Coolant equipment

排削器 2个纵向鹅颈式+1个横向鹅颈式
Chip conveyors
2 longitudinal + 1 cross goose neck

ZAYER
www.zayer.com