

# ZAYER

## ARION G 2000

龙门加工中，固定横梁和移动工作台

Bridge type machining center, fixed cross beam and moving table



规格

### TECHNICAL SPECIFICATIONS

纵向行程 Longitudinal travel	mm	3500
横向行程 Cross travel	mm	3100
垂直向行程 Vertical travel	mm	1100
铣/回转工作台 Milling / turning rotary table	Mm	3000 x 2000
立柱间距离 Distance between columns		Ø 2000
工作台到主轴鼻端最大距离 Max. distance from table to spindle nose	mm	970
工作进给 Working feed	mm/min	达到/ up to 15000
快速进给 Rapid feed	mm/min	30000
铣头 Head		电主轴 45°持续旋转 45° continuous rotation with electrospindle
功率 Power	kW	42
主轴头速度 Speed of the spindle head	min <sup>-1</sup>	15000
刀库 Tool magazine		30 / HSK-A100
冷却设备 Coolant equipment		两个 6-37 bar 和 5bar 的泵，容量为 1000l Two pumps of 6-37 and 5 bar, 1000 l
排屑器 Chip conveyor		2 个纵向鹅颈式+1 个横向鹅颈式 2 longitudinal + 1 cross goose neck
CNC 数控系统		Siemens 840 Dsl