



Product information:

20KF / 20KFU

BED TYPE

SPECIFICATIONS

	20KF
Table length - mm	3.000 - 5.000
Table width - mm	1.000 (1.300)*
Longitudinal travel - mm	2.700 - 4.700
Cross travel - mm	1.250 (1.500)*
Vertical travel - mm	1.000 (1.500)*
Min – max distance from table to spindle nose - mm	0-934 (1.434)*
Rapid feed - mm/min	20.000
Working Feed - mm/min	6 - 10.000
Drives of X,Y,Z, axis	X: B / 80 Y: B / 80 Z: B / 80
B= Ball screw / Ø mm	
R= Rack / Module	
Power - kW	28
Speed of the spindle head - min-1	35-3.000 (4.500-6.000)*
Positioning and repeatability accuracy - mm	0,008/4.000 0,005/4.000
Tool magazine	30 (40-60-80-100)* -
Allowed weight on the table - kg	10.000
Approx. net weight - kg	24.000 - 34.000

(Optional) *

ACCESSORIES

	20KF
HEADS	
45° automatic head 360.000 positions	• ○
Direct Outlet head	○
Movable quill Ø 175 x 500 mm	—
Change of heads	○
Change of Pallets	—
Chip Conveyor	○
Coolant tank 22 + 5 bar	500l 60l/min 2,5bar

- Standard
- Optional
- No available

HEAD IMAGES



45° automatic head



Direct Outlet head

Más información en www.zayer.com