

Product information:

30KM / 30KMU

MOVING COLUMN

SPECIFICATIONS

	30KM	30KMU
Table length - mm	3.700-4.700	
Table width - mm	1.200	
Longitudinal travel - mm	2.400-3.400	
Cross travel - mm	1.250 (1.600)*	
Vertical travel - mm	1.500 (2.000)*	
Min – max distance from table to spindle nose - mm	0-1.445 (1.945)*	
Working Feed - mm/min	6 - 10.000	
Rapid feed - mm/min	20.000	
Drives of X,Y,Z, axis	X: B / 80	
B= Ball screw / Ø mm	Y: B / 80	
R= Rack / Module	Z: B / 80	
Power - kW	37	
Speed of the spindle head - min ⁻¹	35-3.000 (4.500-6.000)*	
Positioning and repeatability accuracy - mm	0,008/4.000 0,005/4.000	
Tool magazine	-	30 (40-60-80)*
Platform for the operator	-	
Allowed weight on the table - kg	3.500 / m ²	
Approx. net weight - kg	36.000-68.000	

(Optional) *

ACCESSORIES

	30KM	30KMU
HEADS		
45° Manual Head	•	—
45° Automatic Head 360.000 pos, 0,001°	○	•
Movable Quill	○ Ø 175 x 500 mm	
Direct Outlet head	○	
Change of heads	○	
Coolant tank	○	

30KM | **30KMU**

Chip Conveyor

○

- Standard ○ Optional — No available

PRODUCT IMAGES



Protecciones CE



Protecciones CE y
Mampara de separacion
para trabajo pendular

HEAD IMAGES




45° Manual Head



45° Automatic Head
360.000 pos, 0,001°



Direct Outlet head



Direct outlet head with
quill



Extended "L" shaped
head with manual change
of tool

RELATED APPLICATIONS

Más información en www.zayer.com