



Product information:

TEBAS
BRIDGE TYPE

SPECIFICATIONS

	TEBAS
Table length - mm	4.100 – 6.100
Table width - mm	2.200 (2.500 - 3.000)*
Distance between columns - mm	3.000 (3.500 - 4.000)*
Longitudinal travel - mm	4.000 - 6.000
Cross travel - mm	3.750 (4.250)*
Vertical travel - mm	1.250 (1.500)*
Max. distance from table to spindle nose - mm	1.465 (1.765)*
Working Feed - mm/min	up to 30.000
Rapid feed - mm/min	50.000
Drives of X-Y-Z - mm	X,Y: Two motors rack and pinion Z: 2 Ball screws
Power - kW	43
Speed of the spindle head - min ⁻¹	4.500 - 6.000
Positioning and repeatability accuracy - mm	0,008/4.000-0,005
Tool magazine	30 (40-60-80)*
Allowed weight on the table - kg	20.000
Approx. net weight - kg	40.000 - 85.000

(Optional) *

ACCESSORIES

	TEBAS
HEADS	
45° Automatic Head 360.000 pos, 0,001°	•
30° automatic head 360.000 pos. 0,001°	○
30° automatic head, 360.000 positions each 0,001° / continuous rotation with electrospindle.	○
Direct Outlet head	○
Extended "L" shaped head	○
Change of heads	•
Coolant tank	1.000 l - 30 l/min - 22 bar 60 l/min - 5 bar

TEBAS

Chip Conveyor

- Standard
- Optional
- No available

PRODUCT IMAGES



HEAD IMAGES



45° Automatic Head
360.000 pos, 0,001°



30° automatic head
360.000 pos. 0,001°



30° automatic head,
360.000 positions each
0,001° / continuous
rotation with
electrospindle.



Direct Outlet head



Extended "L" shaped
head

RELATED APPLICATIONS



**INVAR MOULD
FIXTURE**
AERONAUTIC




STRUCTURALS PARTS
AERONAUTIC




ROTOR
WIND ENERGY



BOGIE
RAILWAY



CAPITAL GOODS
GENERAL MACHINING



MACHINE TOOL
GENERAL MACHINING



MOULD
MOULDS AND DIES



DIE
MOULDS AND DIES



CAPITAL GOODS
LARGE COMPONENTS

Más información en www.zayer.com