



Product information:

MEMPHIS

GANTRY

SPECIFICATIONS

	MEMPHIS	MEMPHIS U
Table length - mm	2.500 – 3.500 ... 19.500	
Table width - mm	2.000 (3.000-4.000)*	
Distance between columns - mm	3.000 (4.000-5.000)*	
Longitudinal travel - mm	3.000 - 4.000 ... 20.000	
Cross travel - mm	2.000 (3.000-4.000)*	
Vertical travel - mm	1.250 (1.500)*	
Max. distance from table to spindle nose - mm	1.465 (1.715)*	
Rapid feed - mm/min	50.000	
Working Feed - mm/min	up to 20.000	
Drives of X-Y-Z - mm	X,Y: Two motors rack and pinion Z: 2 Ball screws	
Power - kW	43	
Speed of the spindle head - rpm	4.500 - 6.000	
Positioning and repeatability accuracy - mm	0,008/4.000-0,005	
Tool magazine	30 (40-60-80)*	
Allowed weight on the table - kg/m ²	15.000	
Approx. net weight - kg	55.000 - 235.000	

(Optional) *

ACCESSORIES



	MEMPHIS	MEMPHIS U
HEADS		
Direct Outlet head	○	
"L" shaped head	○	
45° head 360.000 positions, 0,001° / continuous rotation	•	
30° head, positioning / continuous rotation	○	
Change of heads	•	
Chip Conveyor	•	
Coolant tank 22 + 5 bar	1.000 l, 30 l/min - 22 bar / 60 l/min - 5 bar	

- Standard
- Optional
- No available

PRODUCT IMAGES



Memphis doors open



HEAD IMAGES



45° automatic head
360.000 positions, 0,001°



30° automatic head
360.000 pos. 0,001°



Direct Outlet head

RELATED APPLICATIONS



AERONAUTIC



RAILWAY



MOULDS AND DIES

Más información en www.zayer.com