



Product information:

KAIROS P
MOVING COLUMN

SPECIFICATIONS

	KAIROS P
Longitudinal travel - mm	3.000 - 15.000
Cross travel - mm	1.600 (2.000)*
Vertical travel - mm	4.500 (5.000-6.000-7.000-8.000)*
Working Feed - mm/min	Up to 10.000
Longitudinal rapid feed - mm/min	15.000 (depending on vertical travel)
Cross rapid feed - mm/min	25.000
Vertical rapid feed - mm/min	15.000 (depending on vertical travel)
Drives of X axis - mm	two motors rack and pinion
Power - kW	74
Speed of the spindle head - min ⁻¹	3.000 (4.500)*
Positioning and repeatability accuracy - mm	0,008/4.000
	- 0,005
Tool magazine	30 (40-60-80-100-120)*
Platform for the operator	Fixed to the longitudinal carriage. (Autonomous with vertical displacement)*

(Optional) *

ACCESSORIES

	KAIROS P
HEADS	
45° Automatic Head 360.000 pos, 0,001°	•
30° automatic head continuous rotation	○
Change of heads	○
Fixed floor table	○
Rotary table	○
Chip Conveyor	○

• Standard ○ Optional — No available

HEAD IMAGES



45° Automatic Head
360.000 pos, 0,001°



Direct Outlet head

RELATED APPLICATIONS



CAPITAL GOODS
LARGE COMPONENTS

Más información en www.zayer.com