



## Product information:

# ARSEN

BRIDGE TYPE

## SPECIFICATIONS

|                                               | ARSEN                             |
|-----------------------------------------------|-----------------------------------|
| Table length - mm                             | 4.100 - 5.100 - 6.100..... 10.100 |
| Table width - mm                              | 2.500 (3.000-3.500-4.000-4.500)*  |
| Distance between columns - mm                 | 3.500 (4.000-4.500-5.000)*        |
| Longitudinal travel - mm                      | 4.000-5.000-6.000 .... 10.000     |
| Cross travel - mm                             | 4.250 (4.750)*                    |
| Vertical travel - mm                          | 1.250 (1.500 - 2.000)*            |
| Max. distance from table to spindle nose - mm | 1.465 (1.965)*                    |
| Rapid feed - mm/min                           | X=25.000; Y,Z=30.000              |
| Working Feed - mm/min                         | X=up to 15.000; Y,Z=up to 20.000  |
| Power - kW                                    | 74                                |
| Speed of the spindle head - min-1             | 4.500                             |
| Positioning and repeatability accuracy - mm   | 0,008/4.000-0,005                 |
| Tool magazine                                 | 30 (40-60-80)*                    |
| Allowed weight on the table - kg              | 20.000 - 45.000                   |
| Approx. net weight - kg                       |                                   |

(Optional) \*

## ACCESSORIES

|                                                         | ARSEN |
|---------------------------------------------------------|-------|
| HEADS                                                   |       |
| 30° head with electrospindle, 360.000 positions         | ○     |
| Direct Outlet head                                      | ○     |
| 45° head 360.000 positions, 0,001° / continous rotation | •     |
| Change of heads                                         | •     |
| Chip Conveyor                                           | •     |
| Rotary table                                            | ○     |

• Standard    ○ Optional    — No available

PRODUCT IMAGES



HEAD IMAGES



45° automatic head  
360.000 positions, 0,001°




30° head with  
electrospindle



Direct Outlet head

RELATED APPLICATIONS



CROSS RAIL  
RAILWAY

Más información en [www.zayer.com](http://www.zayer.com)