



Product information:

ARGUS
GANTRY

SPECIFICATIONS

	ARGUS
Table length - mm	3.500-20.500
Table width - mm	2.000 (3.000-4.000)*
Distance between columns - mm	3.000 (4.000-5.000)*
Longitudinal travel - mm	3.000-20.000
Cross travel - mm	3.750 (4.750-5.750)*
Vertical travel - mm	1.250 (1.500 - 2.000)*
Max. distance from table to spindle nose - mm	1.570 (1.820 - 2.070)*
Working Feed - mm/min	up to 20.000
Rapid feed - mm/min	X: 20.000 - Y,Z: 30.000
Drives of X-Y-Z - mm	two motors rack and pinion
Power - kW	74
Speed of the spindle head - min ⁻¹	4.500
Positioning and repeatability accuracy - mm	0.008/4000-0.005
Tool magazine	30 (40-60-80)*
Allowed weight on the table - kg	15.000 kg/m ²
Approx. net weight - kg	50.000 - 110.000

(Optional) *

ACCESSORIES

	ARGUS
HEADS	
45° Automatic Head 360.000 pos, 0,001°	•
30° automatic head 360.000 pos. 0,001° / continuous rotation	○
30° automatic head, 360.000 positions each 0,001° / continuous rotation with electrospindle.	○
	○
Change of heads	○
Coolant tank	•
Chip Conveyor	•

- Standard
- Optional
- No available

PRODUCT IMAGES



HEAD IMAGES



45° Automatic Head
360.000 pos, 0,001°



30° automatic head
360.000 pos. 0,001° /
continuous rotation



30° automatic head,
360.000 positions each
0,001° / continuous
rotation with
electrospindle.



Direct Outlet head

RELATED APPLICATIONS



RAIL
RAILWAY



BOGIE
RAILWAY



CAPITAL GOODS
LARGE COMPONENTS

Más información en www.zayer.com