

Product information:

ARION
BRIDGE TYPE

SPECIFICATIONS

	ARION
Table length - mm	3000 - 4000 mm
Table width - mm	1600 (2000)*
Distance between columns - mm	2000 (2500)*
Longitudinal travel - mm	3000 - 4000 mm
Cross travel - mm	2600 (3100)*
Vertical travel - mm	1100
Max. distance from table to spindle nose - mm	1510
Working Feed - mm/min	up to 15000
Rapid feed - mm/min	30000
Drives of X-Y-Z - mm	Ball screw
Power - kW	24
Speed of the spindle head - min ⁻¹	6000
Positioning and repeatability accuracy - mm	0,008/4000
	- 0,005
Tool magazine	20 (30-40)*
Approx. net weight - kg	35.000 - 50.000

(Optional) *


ACCESSORIES

	ARION
HEADS	
45° Automatic Head 360.000 pos, 0,001°	—
30° automatic head 360.000 pos. 0,001°	•
30° automatic head continuous rotation	○
30° automatic head, 360.000 positions each 0,001° and/or continuous rotation with electrospindle.	○
Direct Outlet head	○
Change of heads	○
Coolant tank	800 l, 30 l/min - 20 bar / 60 l/min - 5 bar

	ARION
Rotary table	○
Chip Conveyor	•

• Standard ○ Optional — No available

PRODUCT IMAGES



HEAD IMAGES



30° automatic head
360.000 pos. 0,001°



30° automatic head,
360.000 positions each
0,001° and/or continuous
rotation with
electrospindle.



Direct Outlet head

RELATED APPLICATIONS



AERONAUTIC MODEL
AERONAUTIC

Más información en www.zayer.com