



Product information:

ZERO G / ZERO G-MT

BED TYPE

SPECIFICATIONS

	ZERO G / ZERO G-MT
Longitudinal travel - mm	2.000
Cross travel - mm	1.200
Vertical travel - mm	1.600
Max. distance from table to spindle nose - mm	1.345
Rapid feed - mm/min	40.000
Working Feed - mm/min	35.000
. Longitudinal axis	ball screw
. Cross axis	ball screw
. Vertical axis	ball screw
Power - kW	33
Speed of the spindle head - rpm	6.000 (8.000)*
. Positioning accuracy - mm	0,006/4.000
. Repeatability accuracy - mm	0,004/4.000
Tool magazine	40 (60)*
Allowed weight on the table - kg	6.000
Rotary table - mm	1.500 x 1.250

(Optional) *

ACCESSORIES

	ZERO G / ZERO G-MT
HEADS	
45° automatic head 360.000 positions	•
45° head continuous rotation	○
30° head, 360.000 positions / continuous rotation	○
ACCESORIES	
Chip Conveyor	•
Coolant tank 22 + 5 bar	•
Rotary table	•
Complete enclosure with ceiling	•

- Standard
- Optional
- No available

HEAD IMAGES



45° automatic head



30° head, 360.000 positions / continuous rotation

Más información en www.zayer.com